



FLOOR

CORTONA™

GLAZED PORCELAIN with REVEAL IMAGING®

 **daltile®**
IMAGINE WHAT'S POSSIBLE™



Above and cover photos feature Tuscan Sun in 13 x 13 and 6-1/2 x 6-1/2 on the floor.

Create Your Own Escape with the Elegant Look of Travertine

Bring the look of rich travertine into your space with Cortona™. This beautiful stone look has the air of olden Tuscan charm with a captivating and contemporary twist. Where ancient history meets the modern age, this tile reflects the organic beauty of travertine stone, featuring chiseled edges and light surface pitting. Choose from a variety of colors, finishes and sizes to create the perfect look.

- **HIGH-END & CLASSIC APPEAL**
 - Rich aesthetic that easily coordinates with most designs and styles
 - Customize with assorted colors, beautiful accents and two available finishes
- **TRAVERTINE DESIGN & ORGANIC TEXTURE**
 - Realistic, natural stone details with strong, shaded veining
 - Chiseled edges and light pitting resembling the texture of natural stone



**PRE-CONSUMER
RECYCLED MATERIALS**



REVEAL IMAGING®

**CERTIFIED
PORCELAIN
TILE**

U.S. PAT. & TRADEMARK OFFICE

FIELD TILE



WHITE FLORA CR14



TUSCAN SUN CR15



MEDITERRANEAN SAND CR16



UMBRIAN HILL CR17

4 x 13 DECORATIVE ACCENTS



WHITE FLORA CR14



TUSCAN SUN CR15



MEDITERRANEAN SAND CR16









UMBRIAN HILL CR17

CORTONA™

GLAZED PORCELAIN with REVEAL IMAGING®

SIZES

			Thickness	Sq. Ft. per Carton	Pieces per Carton
	20 x 20 Field Tile	(19-11/16" x 19-11/16") (50.00 cm x 50.00 cm)	3/8"	13.46	5
	16 x 24 Field Tile*	(16-1/16" x 24-3/16") (40.80 cm x 61.40 cm)	3/8"	13.49	5
	13 x 20 Field Tile	(13-1/8" x 19-11/16") (33.30 cm x 50.00 cm)	3/8"	12.60	7
	13 x 13 Field Tile	(13-1/8" x 13-1/8") (33.30 cm x 33.30 cm)	3/8"	15.50	13
	6-1/2 x 6-1/2 Field Tile	(6-1/2" x 6-1/2") (16.50 cm x 16.50 cm)	3/8"	10.77	36
	4 x 13 Decorative Accent	(3-15/16" x 13-1/8") (10.00 cm x 33.30 cm)	3/8"	--	16

* Available in unpolished and light polished surface.

FLOOR APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level- Interior	N/A	✓
Wet & Level- Interior	0.42	✓*
Exterior Applications; Pool Decking & Other Wet Areas with Minimal Footwear	0.60	
Ramps & Inclines	0.65	

A DCOF value of 0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSIA 1371-2012, Section 9.6. For more information about DCOF and the DCOF AcuTest®, visit dalTile.com/DCOF.

OTHER APPLICATIONS


	Suitable
Walls/Backsplashes	✓
Countertops	✓**
Pool Linings	

APPLICATION NOTES:

- * Unpolished surface only
- ** 6-1/2 x 6-1/2 field tile only


Light polished surface is suitable only for dry and level floor applications. Suitable for exterior applications in freezing and non-freezing climates when proper installation methods are followed.

TRIM

Type	Number	Size	Pieces per Carton
 Bullnose	S-43E9	3 x 13	30

Bullnose trim is intended to coordinate with floor field tile in the standard 90-degree installation position.

INSTALLATION

Grout Joint Recommendation	Shade Variation
3/16" overlap should not exceed 33% when installing in a staggered brick-joint pattern)	 Random (V4)

TEST RESULTS

	ASTM #	Result
Water Absorption	C373	< 0.5%
Breaking Strength	C648	> 450 lbs
Scratch Hardness	MOHS	8.0
Chemical Resistance	C650	Resistant
Abrasion Resistance	C1027	4

For additional information, visit dalTile.com/information/TestResults.

NOTES

Manufacturer Advisory: Tiles with light polished surface have a dynamic coefficient of friction < 0.42 as measured by the DCOF AcuTest method. Tiles with DCOF values < 0.42 are not recommended for use in areas with wet or slippery conditions. For more information, see ANSI standard A1371 section 6.2.2.1.10, available at www.tileusa.com.

Special consideration needs to be given when installing tiles greater than 15 inches. Please refer to dalTile.com/LargeTiles for more information.

Use of a latex modified thin-set is recommended for installation.

Strong random shading enhances the natural beauty of this product. To achieve optimal results, tile should be selected from multiple cartons and shading arranged planned prior to installation.

Since there are variations in all fired ceramic products, tile and trim supplied for your particular installation may not match these samples. Final color selection should be made from actual tiles and trim and not from tile samples or color reproductions. Manufactured in accordance with ANSIA 1371 standards.

Water, oil, grease, etc. create slippery conditions. For applications with exposure to these conditions require extra caution in product selection. Not for use on ramps.

For additional information refer to "Factors to Consider" at dalTile.com/Factors.



DESIGNED TO HELP EARN LEED™ CREDENTIALS. For more detailed information, visit dalTilegreenworks.com.

SCAN QR CODE FOR PRODUCT INFORMATION

Get a QR Code reader at: GETDALTILE.COM



7834 C.F. Hawin Freeway, Dallas, Texas 75217 | 1.800.933.TILE

To view the complete collection of DalTile® products and information, visit our website at dalTile.com.



IMAGINE WHAT'S POSSIBLE™

© 2016 Dal-Tile Corporation (7/16)